

SPIRAL
LADDER

ACCESSORIES
STAIRS



FILE 5.18
VERSION 4. 13/02/2026

COD. AS**ESCESP



TECHNICAL SPECIFICATIONS

Staircase with alternating steps to facilitate access to the silo eave.

It has landing platforms every two heights (2240 mm). The standard requires a landing every 3 metres at most.

It has grid floor as standard. It has been updated so that the ladder reaches the eave of the silo. It now also has an internal handrail and a higher skirting board, providing greater safety for the operator. Finally, it can also be assembled clockwise or anti-clockwise, depending on the requirements of the project.

INCOMPATIBILITIES For SCE silos, adjustments will need to be made during assembly.



PARTS AND MATERIALS

- 1** INTERMEDIATE PLATFORM
 - Dimensions: 1200x690 or 1000x690 mm
 - Every 2280 mm according to the rule EN ISO 14122
 - Material: grid 30x30
- 2** RUNG
 - Dimensions: 270x690 mm
 - Material: grid 30x30
- 3** HANDRAIL
 - Curved pipe $\varnothing 48 \times 1.5 \times 3000$ mm
 - Material: galvanised steel S280GD Z 275
- 4** TOEPLATE
 - Material: galvanised steel S280GD Z 600 e= 2 mm
- 5** SUPPORT
 - Material: galvanised steel S280GD Z 600 e= 3 mm
- 6** ARTICULATED ELBOWS
 - Material: Polypropylene.

