

ROOF
INSPECTION DOOR

ACCESSORIES
ROOF



FILE 5.4
VERSION 3. 14/06/2021

COD. ASPUERTECH



TECHNICAL SPECIFICATIONS

Door to go into the silo. Dimensions 610 x 700mm

To be installed it's necessary to open the hole over a standard roof sector.

It has a block system over the handle.

Usually it's installed with an inside ladder, but the ladder it's not a standard accessory.

It's a standard accessory that doesn't supply to the manhole.

PARTS AND MATERIALS

- 1 ROOF ACCESS DOOR FLANGE
 - Access door's frame
 - MATERIAL: Galvanised steel S275 JR e= 3mm
- 2 ROOF ACCESS DOOR COVER
 - Access door's cover
 - MATERIAL: Galvanised steel S275 JR e= 2mm
- 3 ROOF ACCESS DOOR FLANGE-HINGE
 - Bent sheet joined to roof access door flange and roof access door cover
 - MATERIAL: Galvanised steel S280 GD Z600 MAC e= 3mm
- 4 LOCK SYSTEM
 - Simple and easy
 - System composed of a wing nut
- 5 WEATHER STRIP
 - Cover placed on the door leaf, to seal its connection with the lid.
 - MATERIAL: rubber